

# SOFAR 7K~10.5KTLM-G3

7/7.7/8/9/10/10.5 kW

## SINGLE-PHASE THREE MPPTS



### Product advantages

- Max. efficiency up to 98.1%
- Low start-up voltage, wide MPPT voltage range
- Three MPPTs with 150% DC overload
- Compatible with 500 W+ modules
- I-V curve scanning function
- Natural cooling, no fans, low noise
- Prolonged AC overload compatibility (110%)



Model	SOFAR 7KTLM-G3	SOFAR 7.7KTLM-G3	SOFAR 8KTLM-G3	SOFAR 9KTLM-G3	SOFAR 10KTLM-G3	SOFAR 10.5KTLM-G3
<b>Input (DC)</b>						
Max. input voltage	600V					
Rated input voltage	360V					
Start-up voltage	90V					
MPPT operating voltage range	80V-550V					
Number of MPP trackers	3					
Number of DC inputs	3					
Max. input MPPT current	20A/16A/16A					
Max. input short circuit current	30A/25A/25A					
<b>Output (AC)</b>						
Rated output power	7000W	7700W	8000W	9000W	10000W	10500W
Max. apparent power	7700VA	7700VA	8800VA	9900VA	10000VA	10500VA
Max. output current	35A	35A	40A	45A	46A	46A
Rated output voltage	L/N/PE,230Vac					
Output voltage range	180Vac-276Vac					
Rated output frequency	50/60Hz					
Output frequency range	45Hz-55Hz/55Hz-65Hz					
Active power adjustable range	0-100%					
THDi	<3%					
Power factor	1 (adjustable +/-0.8)					
<b>Efficiency</b>						
Max. efficiency	98.1%					
European efficiency	97.3%					
<b>Protection</b>						
DC reverse polarity protection	Yes					
Anti-islanding protection	Yes					
Leakage current protection	Yes					
Ground fault monitoring	Yes					
PV-array string fault monitoring	Yes					
DC switch	Yes					
SPD	PV: type II, AC: type III					
<b>General Data</b>						
Ambient temperature range	-30°C~+60°C					
Self-consumption at night	<1W					
Topology	Transformerless					
Degree of protection	IP65					
Allowable relative humidity range	0-100%					
Max. operating altitude	4000m					
Cooling	Natural					
Dimension(W*H*D)	468*380*187 mm					
Weight	17.5kg			18.5kg		
Display	LCD & Bluetooth +APP					
Communication	RS485/WiFi					
Standard	IEC/EN 61000-6-1/3, IEC/EN 61000-3-11/12, IEC 62116, IEC 61727, IEC 61683, IEC 60068-1/2/14/30, IEC/EN 62109-1/2, G99, VDE V 0126-1-1, EN 50549-1, ANRE 208					

\*All specifications are subject to change without notice.